

Flat Concrete Substrate




Sound Tested in Accordance
with ASTM E90-09

PT11 – Vertical Wall to Wall Gypsum to Concrete Column

Fire Rated Gasket (FRG) - UL Listing: [WW-S-0089](#) – STC 55
Smoke-n-Sound Gasket (SSG) – WEAL Report: [TL17-288](#) – STC 54

Fire Rated	Smoke-n-Sound	Strip Width	Max. Joint Protection
FRG-75	SSG-75	1.00"	.75"
FRG-100	SSG-100	1.25"	1.00"
FRG-150		1.75"	1.50"
FRG-200		2.25"	2.00"



1. Installed Gap = **Deflection Joint Protection**
2. Attach to substrate with approved fastener max 24" O/C or per E.O.R.
3. Drywall fasteners installed per U, V, or W400 series UL design
4. Fire Rated (FRG) install and overlap per UL listed assembly or Safti-Seal install guide
5. Sound Gasket (SSG) install per WEAL test report

UL, ASTM & Code Standards

UL2079 (5th Edition) & CAN/ULC S115
ASTM E814, E1966, E2837
A1003, A653, A924, C645, C754, C955
Sound Tested according to ASTM E90-09
2012 & 2015 IBC

Leed Points

MR 2.1 & 2.2 - Construction Waste: up to 2pts
MR 4.1 & 4.2 - Recycled Content: up to 2 pts
MR 5.1 & 5.2 - Regional Proximity
EQ 4.1 - Low Emitting Materials
EQ 9 - Enhanced Acoustical

Phone: (425) 869-2811 Fax: (425) 869-2300

www.saftiseal.com