

# Vertical & Miscellaneous




Sound Tested in Accordance  
with ASTM E90-09

## VM10 – Bottom of Wall

Fire Rated Gasket (FRG) - UL Listing: [BW-S-0055](#) – *STC 55*  
Smoke-n-Sound Gasket (SSG) – WEAL Report: [TL17-288](#) – *STC 54*

| Fire Rated | Smoke-n-Sound | Strip Width | Max. Joint Protection |
|------------|---------------|-------------|-----------------------|
| FRG-75     | SSG-75        | 1.00"       | .75"                  |



1. Installed Gap = joint protection (JP) of profile
2. Attach to substrate with approved fastener max 24" O.C or per E.O.R
3. Fire Rated (FRG) install and overlap per UL listed assembly or Safti-Seal install guide
4. Sound Gasket (SSG) install per WEAL test report

### UL, ASTM & Code Standards

UL2079 (5<sup>th</sup> Edition) & CAN/ULC S115  
ASTM E814, E1966, E2837  
A1003, A653, A924, C645, C754, C955  
Sound Tested according to ASTM E90-09  
2012 & 2015 IBC

### Lead Points

MR 2.1 & 2.2 - Construction Waste: up to 2pts  
MR 4.1 & 4.2 - Recycled Content: up to 2 pts  
MR 5.1 & 5.2 - Regional Proximity  
EQ 4.1 - Low Emitting Materials  
EQ 9 - Enhanced Acoustical

Phone: (425) 869-2811 Fax: (425) 869-2300  
U.S. Patent #10,626,598